

# WHAC.E42363 - SWITCHES FOR APPLIANCES

## Switches for Appliances

See General Information for Switches for Appliances

### C & K COMPONENTS INC

15 RIVERDALE AVE  
NEWTON, MA 02458-1057 USA

E42363

Cat. No.	Load	Amps	Volts	Hz	T Rating	Pol/ Thr	Endurance Cycles	IP	Dis Full (mm)/ Micro	Pollution Degree	Ball Pressure (°C)	Glow Wire (°C) (t <sub>E</sub> ≤ 2 s)	PTI (V)
<b>Switch</b>													
<i>MPS45WGW</i>	R	0.100	50	50/60	75	1/1	1E5	40	Micro	3	125	850	250
	R	0.100	50	DC	75	1/1	1E5	40					
	R	0.250	20	50/60	75	1/1	1E5	40					
	R	0.250	20	DC	75	1/1	1E5	40					
9201	GP	6	125	50/60	85	2/2	1E4	00	Full 3.5	2	125	850	600, 400
	GP	3	250	50/60	85	2/2	1E4	00					
	R	6	30	DC	85	2/2	1E4	00					
9221	GP	10	125	50/60	85	2/2	1E4	00	Full 3.5	2	125	850	600, 400
	GP	5	250	50/60	85	2/2	1E4	00					
	R	10	30	DC	85	2/2	1E4	00					
9121	GP	10	125	50/60	85	1/2	1E4	00	Full 3.5	2	125	850	600, 400
	GP	5	250	50/60	85	1/2	1E4	00					
	R	22	36	DC	85	1/2	1E4	00					

	R	13	60	DC	85	1/2	1E4	00						
9122	GP	10	125	50/60	85	1/1	1E4	00	Full 3.5	2	125	850	600, 400	
	GP	5	250	50/60	85	1/1	1E4	00						
	R	22	36	DC	85	1/1	1E4	00						
	R	13	60	DC	85	1/1	1E4	00						
V701, -702, -801 and -802	R-M	2(0.5)	250	50/60	85	1,2/1,2	1E4	00	Full 4.4	2	125	850	175	
	GP	10	125	50/60	85	1,2/1,2	1E4	00						
	GP	5	250	50/60	85	1,2/1,2	1E4	00						
	R	4	30	DC	85	1,2/1,2	1E4	00						
DM21, DM22, DM14, DM24	GP	3	125	50/60	85	M/M	1E4	00	Full 2.5	2	125	850	400, 600	
	GP	2	250	50/60	85	M/M	1E4	00						
	R	3	30	DC	85	M/M	1E4	00						
DM61, DM62, DM54, DM64	GP	10	125	50/60	85	M/M	1E4	00	Full 2.5	2	125	850	400, 600	
	GP	5	250	50/60	85	M/M	1E4	00						
	R	10	30	DC	85	M/M	1E4	00						
D101, D102 D103, D105 D108, D201 D202, D203	GP	4	125	50/60	85	M/M	1E4	00	Full 2.5	2	125	850	400, 600	
	GP	2	250	50/60	85	M/M	1E4	00						
	R	4	30	DC	85	M/M	1E4	00						
D501, D502 D503, D508, D601, D602 D608	GP	10	125	50/60	85	M/M	1E4	00	Full 2.5	2	125	850	400, 600	
	GP	5	250	50/60	85	M/M	1E4	00						
	R	10	30	DC	85	M/M	1E4	00						
NE18 f/b 2U, 2A, S, X, W or P	GP	8	125	50/60	70	2/1,2	1E4	00	Full 2.0	2	125	850	175, 600	
	GP	6	250	50/60	70	2/1,2	1E4	00						
	R-M	6(4)	250	50/60	70	2/1,2	1E4	00						
	R-C	6/48	250	50/60	70	2/1,2	1E4	00						
	R	1	100	DC	70	2/1,2	1E4	00						
	R	8	30	DC	70	2/1,2	1E4	00						

<i>NE18CTII f/b 2U, 2A, S, X, W or P</i>	GP	4	250	50/60	70	2/1,2	1E4	00	Full 2.0	2	125	850	175, 600
	R-C	4/48	250	50/60	70	2/1,2	1E4	00					
	R	1	100	DC	70	2/1,2	1E4	00					
	R	4	30	DC	70	2/1,2	1E4	00					
<i>LCX1</i>	GP	1	250	50/60	85	1/1,2	25E3	00	Micro	2	125	850	175
	R	1	30	DC	85	1/1,2	1E4	00					
<i>LCV6</i>	R-M	5(2)	250	50/60	85	1/1,2	1E4	00	Micro	2	125	850	175
	GP	5	250	50/60	85	1/1,2	1E4	00					
	R	5	30	DC	85	1/1,2	1E4	00					
	HP	1/3	125/250	50/60	85	1/1,2	1E4	00					
<i>LCV7</i>	R-M	10(2)	250	50/60	85	1/1,2	1E4	00	Micro	2	125	850	175
	GP	10	250	50/60	85	1/1,2	1E4	00					
	R	10	30	DC	85	1/1,2	1E4	00					
	HP	1/3	125/250	50/60	85	1/1,2	1E4	00					
<i>DS2, f/b F5, f/b A, B, C, D or E, f/b Q1, Q2, Q3, Q4, Q5, Q6, Q7 or Q8, f/b BK or blank</i>	GP	0.1	125/250	50/60	85	2/1	5E4	40	Full 1.6	2	125	750	400
	R-M	0.1(0.5)	125/250	50/60	85	2/1	5E4	40					
	GPM	0.5(0.5)	125/250	50/60	85	2/1	5E4	40					
<i>DS2, f/b F7, f/b A, B, C, D or E, f/b Q1, Q2, Q3, Q4, Q5, Q6, Q7 or Q8, f/b BK or blank</i>	GP	0.1	125/250	50/60	85	2/1	1E5	40	Full 1.6	2	125	750	400
	R-M	0.1(0.5)	125/250	50/60	85	2/1	1E5	40					
	GPM	0.5(0.5)	125/250	50/60	85	2/1	1E5	40					
<i>DS2, f/b D6, f/b A, B, C, D or E, f/b Q1, Q2, Q3, Q4, Q5, Q6, Q7 or Q8, f/b BK or blank</i>	GP	10	125/250	50/60	85	2/1	1E4	40	Full 1.6	2	125	750	400
	R-M	10(4)	125/250	50/60	85	2/1	5E4	40					
	HP	1/3	250	50/60	85	2/1	1E4	40					
	HP	1/3	125	50/60	85	2/1	1E4	40					
<i>DS2, f/b D7, f/b A or B, f/b</i>	GP	16	125/250	50/60	85	2/1	1E4	40	Full 1.6	2	125	750	400
	R-M	16(6)	125/250	50/60	85	2/1	1E4	40					

Q3, f/b BK or blank	HP	3/4	250	50/60	85	2/1	1E4	40						
	HP	3/4	125	50/60	85	2/1	1E4	40						
DS1, f/b F5, f/b A, B, C, D or E, f/b Q1, Q2, Q3, Q4, Q5, Q6, Q7 or Q8, f/b BK or blank	GP	0.1	125/250	50/60	85	2/1	5E4	40	Full 1.6	2	140.3	750	400	
	R-M	0.1(0.5)	125/250	50/60	85	2/1	5E4	40						
	GPM	0.5(0.5)	125/250	50/60	85	2/1	5E4	40						
DS1, f/b F7, f/b A, B, C, D or E, f/b Q1, Q2, Q3, Q4, Q5, Q6, Q7 or Q8, f/b BK or blank	GP	0.1	125/250	50/60	85	2/1	1E5	40	Full 1.6	2	140.3	750	400	
	R-M	0.1(0.5)	125/250	50/60	85	2/1	1E5	40						
	GPM	0.5(0.5)	125/250	50/60	85	2/1	1E5	40						
DS1, f/b D6, f/b A, B, C, D or E, f/b Q1, Q2, Q3, Q4, Q5, Q6, Q7 or Q8, f/b BK or blank	GP	10	125/250	50/60	85	2/1	1E4	40	Full 1.6	2	140.3	750	400	
	R-M	10(4)	125/250	50/60	85	2/1	5E4	40						
	HP	1/3	250	50/60	85	2/1	1E4	40						
	HP	1/3	125	50/60	85	2/1	1E4	40						
DS1, f/b D7, f/b A or B, f/b Q3, f/b BK or blank	GP	16	125/250	50/60	85	2/1	1E4	40	Full 1.6	2	140.3	750	400	
	R-M	16(6)	125/250	50/60	85	2/1	1E4	40						
	HP	3/4	250	50/60	85	2/1	1E4	40						
	HP	3/4	125	50/60	85	2/1	1E4	40						
SW-1 f/b 1, 2 or 3; f/b A, f/b 06; f/b F or N; f/b -A, -B, -C, -D, -E, -F, -G, -H, -BR, -CR, -DR, -ER, -FR, -GR or -HR; f/b 02, 03, 04, 05, 06, 07, 08, 09, 10, 11 or 12; f/b number(s) or blank for color	GP	6	125/250	50/60	85/55	1/1,2	1E4	40	Full 1.6	2	125	650	175	
	RA	6	125/250	50/60	85/55	1/1,2	1E4	40						
	RM	6(2)	125/250	50/60	85/55	1/1,2	1E4	40						
	GPM	6GP(2)	125/250	50/60	85/55	1/1,2	1E4	40						
SW-1 f/b 1, 2 or 3; f/b A, f/b 10; f/b F or N; f/b -A, -B, -C, -D, -E, -F, -G, -	GP	10	125/250	50/60	85/55	1/1,2	1E4	40	Full 1.6	2	125	650	175	
	HP	1/3	125	50/60	85/55	1/1,2	1E4	40						
	HP	3/4	250	50/60	85/55	1/1,2	1E4	40						

<i>H, -BR, -CR, -DR, -ER, -FR, -GR or -HR; f/b 02, 03, 04, 05, 06, 07, 08, 09, 10, 11 or 12; f/b number(s) or blank for color</i>	RM	10(8)	125/250	50/60	85/55	1/1,2	1E4	40						
	RM	6(4)	125/250	50/60	85/55	1/1,2	5E4	40						
	RA	10	125/250	50/60	85/55	1/1,2	1E4	40						
<i>SW-2 f/b 1 or 6; f/b A; f/b 10; f/b N; f/b -A, -B, -C, -D, -ER, -CR or -FR; f/b 02, 03, 04, 05, 06, 07, 08, 09, 10, 11, 12, 13, 15 or 16; f/b number(s) or blank for color</i>	RC	8/128	125/250	50/60	85/55	1,2/1	1E4	40	Full 1.7	2	130	850	400	
	RM	10(4)	125/250	50/60	85/55	1,2/1	1E4	40						
	I	10	125/250	50/60	85/55	1,2/1	1E4	40						
	HP	1/2	250	50/60	85/55	1,2/1	1E4	40						
	HP	1/3	125	50/60	85/55	1,2/1	1E4	40						
<i>SW-2 f/b 1 or 6; f/b A; f/b 16; f/b N; f/b -A, -B, -C, -D, -ER, -CR or -FR; f/b 02, 03, 04, 05, 06, 07, 08, 09, 10, 11, 12, 13, 15 or 16; f/b number(s) or blank for color</i>	R	16	125/250	50/60	85/55	1,2/1	1E4	40	Full 1.7	2	130	850	400	
	HP	3/4	250	50/60	85/55	1,2/1	1E4	40						
	HP	1/2	125	50/60	85/55	1,2/1	1E4	40						
<i>PT, f/b 101, 102, 103, 105, 107, 108, 201, 202, 203, 205, 207 or 208; f/b S; f/b S, Q or Z; f/b Q; may be f/b 00 (maintained functions)</i>	GP	15	277	50/60	85	1,2/1,2	1E4	66, 68	Full 1.6	2	125	850, 650	600, 400, 100	
	RM	15(4)	277	50/60	85	1,2/1,2	1E4	66, 68						
	HP	1/2	125	50/60	85	1,2/1,2	1E4	66, 68						
	HP	1	250	50/60	85	1,2/1,2	1E4	66, 68						
<i>PT, f/b 101, 102, 103, 105, 107, 108, 201, 202, 203, 205, 207 or 208; f/b S; f/b S, Q or Z;</i>	GP	10	277	50/60	85	1,2/1,2	1E4	66, 68	Full 1.6	2	125	850, 650	600, 400, 100	
	RM	10(4)	277	50/60	85	1,2/1,2	1E4	66, 68						

<i>f/b Q; may be f/b 00 (momentary functions)</i>	HP	1/4	125	50/60	85	1,2/1,2	1E4	66, 68						
	HP	1/2	250	50/60	85	1,2/1,2	1E4	66, 68						
<i>L Series (see Nomenclature)</i>	GP	4	125	50/60	65	1,2/M	1E4	00	Micro	2	125	850	400	
	GP	2	250	50/60										
	R	0.5	125	DC										
	R	4	28	DC										

Last Updated on 2018-10-17

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"